

## Nordic Tile

|                     |                             |        |
|---------------------|-----------------------------|--------|
| Tuft Gauge          | 1/10 loop pile              |        |
| Pile Composition    | 100 % PA SDN                |        |
| Primary Backing     | Non Woven                   |        |
| Secondary Backing   | Bitumen                     |        |
| Width               | 50x50 cm                    | ± 1 %  |
| Pile height         | 3,5 mm                      |        |
| Pile weight         | 550 gr/m <sup>2</sup>       |        |
| Total weight        | 3540 gr/m <sup>2</sup>      | ± 15 % |
| Total height        | 6 mm                        |        |
| Number of knots     | 181240 m <sup>2</sup>       |        |
| Use Area            | Extrem / Heavy (33)         |        |
| GUT nr              | E668329F GUT                |        |
| Sound isolation     | ca. 25 dB                   |        |
| Thermal resistance  | ca. 0,07 m <sup>2</sup> Kw  |        |
| Light fastness      | ≥ 5                         |        |
| Wearability         | ≥ 4                         |        |
| Water fastness      | ≥ 4                         |        |
| Fire Classification | Bfl-S1 1658-CPR-3134        |        |
| Comments            | Noise absorption ca 0,15 aW |        |

## Symboler



## Certifikat

